

Mixed - Xylene

#	PROPERTY	Units	Test Method	Value
1	Appearance	--	VISUAL	Clear , Free of Haze / Sediment
2	Density @ (15.6°C)	gr/cm ³	ASTM D-4052	To Be Reported
3	Color , pt-Co Scale	--	ASTM D-1209	10 max.
4	Acid Wash Color	--	ASTM D-848	6 max.
5	Acidity	mgr NaOH/100ml.	ASTM D-847	NO Free Acid
6	Copper Corrosion	--	ASTM D-849	No.1a
7	H ₂ S & So ₂ Content	--	ASTM D-853	Free of (H ₂ S/ SO ₂)
8	Distillation Range @ 760 mmHg	°C	ASTM D-850	5 max.
9	I.B.P	°C	ASTM D-850	137 min.
10	D.P	°C	ASTM D-850	143 max.
11	Para Xylene	wt%	ASTM D-2306	16.5 min.
12	Ortho Xylene	wt %	ASTM D-2306	15 min.
13	Ethyl Benzene	wt %	ASTM D-2306	18.5 max.
14	Metha Xylene	wt %	ASTM D-2360	49 max.
15	Benzene	wt %	ASTM D-2360	0.005 max.
16	Toluene	wt %	ASTM D-2360	0.04 max.
17	C9 Aromatics	wt %	ASTM D-2360	0.5 max.
18	Non Aromatics	wt %	ASTM D-1360	0.05 max.
19	Total Sulfur	wt.ppm	UOP 727	1 max.
20	Total Chlorides	wt.ppm	IP-AK/81	1 max.
21	Bromine Index	mgr/100 gr	IP-129(MODIFIED)	20 max.

Shipping : Bulk carrier