



Arak Petrochemical Company



ISO 9001:2000

Certificate No.: CH98/8032

ISO 14001:2004

Certificate No.: CH03/0112

OHSAS 18001:1999

Certificate No.: CH05/0675

**Address:**

No. 3, Taban St.  
Vali-e-Asr Ave.  
Tehran - IRAN

**Tel:**

(+98 21)82122700

**Fax:**

(+98 21)88674126-27

**Web-site:**

www.arpc.ir

**E-mail:**

Sales@arpc-ir.net

## Diethylene Glycol (DEG)

| Characteristic           | Test Method    | Unit    | Value         |
|--------------------------|----------------|---------|---------------|
| PURITY                   | ASTM E - 202   | WT.%    | 99.8 MIN      |
| MONOETHYLENE GLYCOL      | ASTM E - 202   | WT.%    | 0.05 MAX.     |
| TRIETHYLENE GLYCOL       | ASTM E - 202   | WT.%    | 0.05 MAX.     |
| WATER CONTENT            | ASTM E - 202   | WT.%    | 0.05 MAX      |
| ACIDITY AS ACETIC ACID   | ASTM D - 1613  | PPM     | 50 MAX        |
| ASH CONTENT              | ASTM D - 254/A | PPM     | 50 MAX        |
| SP. GR. (20/20 °C)       | ASTM D - 891   | -       | 1.1175-1.1195 |
| COLOR                    | ASTM D - 1209  | Pt - Co | 10 MAX        |
| DISTILLATION @ 760 MM-Hg |                |         |               |
| IBP                      | ASTM D - 1078  | °C      | 242 MIN       |
| DP                       | ASTM D - 1078  | °C      | 250 MAX       |

**DIETHYLENEGLYCOL** obtained from the reaction of ethylene oxide and MEG. It is a clear, transparent and odorless liquid that can be mixed with water in any proportion.

○ **Application areas:**

• **Resins :**

**DIETHYLENEGLYCOL** is used as synthesizing agent for alkyd resins as well as saturated and unsaturated polyester.

**DIETHYLENEGLYCOL** is used in the synthesis of polyurethane resins, as a coalescence agent, anti-freezing agent in polymer and/or acrylic homopolymer emulsions, chain extender and agent in the dispersion and wetting of unsaturated polyester resins.

• **Synthesizing agents :**

**DIETHYLENEGLYCOL** can be used as synthesis intermediate.

**DIETHYLENEGLYCOL** esters are used as emulsifiers.

**DIETHYLENEGLYCOL** esters with fatty acids (oleic, stearic, lauric, etc.) are used as emulsifiers and plasticizers of polymers.

• **Wetting and plasticizing agents :**

**DIETHYLENEGLYCOL** can be used as wetting and plasticizing agent in the production of cellophane, glues and adhesives, textiles, printing ink, leather, cosmetics, paper and pharmaceutical products.



Arak Petrochemical Company



ISO 9001:2000

Certificate No.: CH98/8032

ISO 14001:2004

Certificate No.: CH03/0112

OHSAS 18001:1999

Certificate No.: CH05/0675

**Address:**

No. 3, Taban St.  
Vali-e-Asr Ave.  
Tehran - IRAN

**Tel:**

(+98 21)82122700

**Fax:**

(+98 21)88674126-27

**Web-site:**

[www.arpc.ir](http://www.arpc.ir)

**E-mail:**

[Sales@arpc-ir.net](mailto:Sales@arpc-ir.net)

## Diethylene Glycol (DEG)

- **Coolant additives :**

**DIETHYLENEGLYCOL** can be used in antifreeze formulations in proportions of up to 10% together with **MONOETHYLENEGLYCOL**. The various quantitative ratios between these components are suitable for specific applications in the field of industrial refrigeration.

- **Cement additive :**

**DIETHYLENEGLYCOL** can be used as an auxiliary additive in cement milling. It can be used in extremely small proportions to produce significant results, increasing the hourly production of cement without increasing the energetic demand on the system.

- **Brake fluids :**

**DIETHYLENEGLYCOL** can be used as secondary solvent in brake fluid formulations. This product is also used to avoid the excessive swelling of rubber in the hydraulic system.

- **Other uses:**

**Ethylene glycols** can also be used in the formulation of printing ink, in the treatment of gases, in the formulation of fire-resistant hydraulic fluids, in the formulation of cutting oils, in the formulation of surface polishers, in the formulations of agrochemicals, in the extraction of solvents, in the manufacture of pigmented pastes and putty for walls, and in the synthesis of explosives.

- **Storage conditions:**

Under nitrogen blanket and at ambient temperature.

- **Packing:**

Bulk or in 220 Lit (net: 220 Kg) new drums, each 4 drums strapped on a pallet.